



KT-2015SH

15-Inch Table Mount PoE Touch Panel



KT-2015SH is a powerful new 10-inch touch panel, specially designed for secure deployments. KT-2010SH is ideal for any 24/7 Kramer-supported commercial AV or control application and features a user-friendly, fully customizable graphical user interface configured by Kramer software. This IPS, multi-touch touch panel with 1920x1200 resolution is elegantly designed for decorative room integration, runs Android 13 and supports PoE (Power over Ethernet). The touch panel comes with tabletop and wall mounts in the box. It is easy to assemble, using elegant wiring, secured mounting providing reliable operation and flexible deployment

FEATURES

Secured Operation - Highly secured operation of applications using password protection and hidden control buttons. Especially designed for high security environments (for example: Military, Ministry of Defense and other law enforcement agencies) where no wireless connectivity (for example Wi-Fi and Bluetooth), no cameras, no speakers and no microphones are required for secure operations

Secured Deployment - Flexible locking options prevent unwanted panel mount removal and are elegantly designed to remain out of sight

Elegant Design - Smooth integration with room furniture design, on table, with flexible panel cabling and locking design options

Superior User Experience - IPS 1920x1200 hi-resolution screen with $\pm 80^\circ$ horizontal and vertical wide viewing angles, ambient light sensor, proximity sensor, with advanced 10 multi-touch points and 2-finger gesture capabilities

Flexible Services - Latest Android 13 Operating System

Easy Installation - Powering and connectivity via a single Ethernet cable

Flexible Mounting - Including table and wall mounts

Versatile Powering Options - PoE and power adapter (sold separately)

Auto Sensing - Optimized performance and operation according to automatically detected LAN speed

Firmware Update - Define automatic updates on a predefined time of the day or update manually using USB port



TECHNICAL SPECIFICATIONS

Ports	1 Ethernet: On an RJ-45 connector, 10/100/1000 Mbps LAN with PoE 802.3at 1 USB: On a USB type C (ADB) connector 1 USB: On a USB Type A connector
General	CPU Performance: ARM Quad-core Cortex-A53 up to 1.8GHz (64 bit) System Memory: 4GB LPDDR4 Internal Storage Memory: 32GB eMMC(flash) Touch Panel Type: 15.1 point capacitive multi-touch type Display Screen: 5 points, multi-touch (PCAP) Display Size 15.1" (16:9 diagonal), 1920 RGB (H) x 1200(V) pixels VESA Mounting Ready: Metal-fittings mounting screw holes for 75x75mm VESA mount Contrast Ratio: 350cd/m2 brightness, 1000:1 Back-light: LED Side-light type
Video	Video Format: H.264 / H.265,VC-1, MPEG-4, VP9/VP8 Image Codecs: JPEG/BMP/GIF/PNG
Power	PoE: Power over Ethernet 802.3af(/at) Source: 12V/2A DC adapter (optional)
User Interface	Controls: Volume, menu, and power buttons Indicators: LED sidebars to indicate room status (requires 3rd party integration)
Accessories	Included: Table mount and wall mount for KT-2015SH
Environmental Conditions	Operating Temperature & Humidity: 0° to +40°C (32° to 104°F), 5% to 85% Storage Temperature & Humidity: -20° to +60°C (-4° to 140°F), 5% to 90%
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC, UL, UKCA Environmental: RoHs, WEEE
PHYSICAL	Product Dimensions: 37.3cm x 2.6cm x 24.3cm (14.6" x 1.02" x 9.5") W,D,H Package Dimensions: 11cm x 48cm x 33cm (4.3" x 18.8" x 13") W, D, H Product Weight: 1.78kg (3.9lbs) approx KT-2015SH Package Weight: 2.83kg (6.2lbs) approx
Product Dimensions	37.30cm x 2.60cm x 24.30cm (14.69" x 1.02" x 9.57") W, D, H
Product Weight	1.8kg (3.9lbs) approx
Shipping Dimensions	11.00cm x 48.00cm x 33.00cm (4.33" x 18.90" x 12.99") W, D, H

Shipping Weight

2.8kg (6.2lbs) approx